

should have the name of the unit plainly marked or painted on its label, except for EPIRBs or SARTs in an inflatable liferaft or permanently installed in a survival craft.

[CGD 84-069, 61 FR 25299, May 20, 1996]

**§ 108.651 Portable magazine chests.**

Each portable magazine chest must be marked: "PORTABLE MAGAZINE CHEST—FLAMMABLE—KEEP LIGHTS AND FIRE AWAY" in letters at least 7.5 centimeters (3 inches) high.

**§ 108.653 Helicopter facilities.**

(a) Each helicopter fueling facility must be marked adjacent to the fueling hose storage: "WARNING—HELICOPTER FUELING STATION—KEEP LIGHTS AND FIRE AWAY".

(b) Each storage tank for helicopter fuel must be marked: "DANGER—FLAMMABLE LIQUID".

(c) Each access to a helicopter landing area must be marked: "BEWARE OF TAIL ROTOR".

(d) Each marking required by this section must be in letters at least 7.5 centimeters (3 inches) high.

**§ 108.655 Operating instructions.**

Each unit must have posters or signs displayed in the vicinity of each survival craft and the survival craft's launching controls that—

(a) Illustrate the purpose of controls;

(b) Illustrate the procedures for operating the launching device;

(c) Give relevant instructions or warnings;

(d) Can be easily seen under emergency lighting conditions; and

(e) Display symbols in accordance with IMO Resolution A.760(18).

[CGD 84-069, 61 FR 25299, May 20, 1996]

**§ 108.657 Unit markings.**

The hull of each unit must be marked in accordance with Parts 67 and 69 of this chapter.

**§ 108.659 Lifesaving signal instructions.**

On all vessels to which this subpart applies, there must be readily available to the offshore installation manager, master, or person in charge a placard containing instructions for the use of

the lifesaving signals set forth in regulation 16, chapter V, of the International Convention for Safety of Life at Sea, 1974. These signals must be used by vessels or persons in distress when communicating with lifesaving stations and maritime rescue units.

[CGD 95-027, 61 FR 26008, May 23, 1996]

**§ 108.661 Unit markings: Draft marks.**

(a) Each unit must have draft marks for each foot of immersion—

(1) If the unit is a surface unit, on both the port and starboard sides of the stem and the stern-post or rudderpost or at any other place at the stern of the unit as may be necessary for easy observance;

(2) If the unit is a self-elevating unit, near each corner of the hull but not more than 4 required; and

(3) If the unit is a column-stabilized unit, on each corner column, continuing to the footing or lower displacement hull.

(b) The bottom of each mark must be at the draft indicated by that mark.

(c) Each mark must be—

(1) In numerals 15 centimeters (6 inches) high; and

(2) In contrasting color to the background.

(d) For the purposes of this section, "draft" means the distance from the bottom of the keel or the lowest shell plate on the outer surface of the unit to the surface of the water, except that where a unit has a permanent appendage extending below the bottom of the keel, "draft" means the distance from the lowest part of the appendage to the surface of the water.

(e) In cases where draft marks are obscured due to operational constraints or by protrusions, the vessel must be fitted with a reliable draft indicating system from which the draft can be determined.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by CGD 89-037, 57 FR 41823, Sept. 11, 1992]

**§ 108.663 Unit markings: Load line.**

Each unit that is assigned a load line must have the load line marked in accordance with Part 42 of this chapter.